



MATERIAL	MIN OPERATING TEMPERATURE	MAX OPERATING TEMPERATURE	UV RESISTANCE	UL FLAME RATING
Nylon 6/6 - Black UV Stabilized	-40°F -40°C	185°F 85°C	Very High	94V-2
Nylon 6/6 - Natural	-40°F -40°C	185°F 85°C	None	94V-2

Kable Kontrol® Assorted Sizes Zip Tie Kits

GAMMA RADIATION RESISTANCE	MILITARY, FEDERAL, AND ASTM SPECIFICATIONS	TENSILE STRENGTH AT 73°F DRY AS MOLDED ASTM-D-638 (PSI)	OXYGEN INDEX %
1x10 Rads	ASTM-D4066 PA181	12,000	24 -28%

CT-KIT-MS-BK Includes 100 Pcs of Each				
Length	Tensile Strength	Strap Width	Max Bundle Diameter	Mil-Spec
4" Long	18 lbs	2.5 mm	1"	MS3367-4-0
5.5" Long	18 lbs	2.5 mm	1.12"	-
8" Long	50 lbs	4.8 mm	2.16"	MS3367-1-0
11" Long	50 lbs	4.8 mm	3.18"	MS3367-7-0



CT-KIT-MS-NT Includes 100 Pcs of Each				
Length	Tensile Strength	Strap Width	Max Bundle Diameter	Mil-Spec
4" Long	18 lbs	2.5 mm	1"	MS3367-4-9
5.5" Long	18 lbs	2.5 mm	1.12"	-
8" Long	50 lbs	4.8 mm	2.16"	MS3367-1-9
11" Long	50 lbs	4.8 mm	3.18"	MS3367-7-9
14" Long	50 lbs	4.8 mm	4.01"	MS3367-2-9